



# Palmetto

Vermiculite Company

## SAFETY DATA SHEET

### SECTION 1 - Chemical Product and Company Identification:

Product Identifier: Vermiculite, All Grades: Masonry Insulation, Attic Insulation, Lightweight Concrete Grade, Pool Base, C-3, C-4, A-2, A-3, A-4  
Product Class: Hydrated Laminar Magnesium Aluminum Iron Silicate  
Product Use: Insulation, Construction, Industrial, and Horticultural Applications

**PALMETTO VERMICULITE COMPANY, INC.**  
**13089 HWY 221 SOUTH- P. O. BOX 178 WOODRUFF SOUTH CAROLINA 29388**  
**Emergency Telephone Number: 800-729-2796**  
**Fax Number: 864-969-2796**

#### Supplier's Name (if different)

- Street Address
- City, Province/State, Postal/Zip Code
- Emergency Telephone Number
- Fax Number

Preparation date of SDS: December 31, 2015 / Revised: 8/20/2015

SDS Prepared By: Phil West (Phone: 800-729-2796)

### SECTION 2 – Hazards Identification:

Route of entry:

Skin contact: Repeated or prolonged contact may cause irritation

Skin absorption: N/A

Eye contact: May irritate or injure eyes, mechanically

Inhalation: Upper Respiratory Irritant: May aggravate pre-existing respiratory conditions.

Long-term inhalation of respirable crystalline silica can cause disabling lung disease. (silicosis).

Ingestion: LD<sub>50</sub> not established, presumed over 2000 mg/kg

Emergency Overview: The fine particle size products represent inhalation hazards that can readily be controlled with appropriate dust protection equipment. Avoid processes that generate unnecessary dust.

WHMIS Symbols:

Potential Health Effects: See above regarding long term exposure: skin irritation, silicosis and eye irritation. Non Hazardous.

### **SECTION 3 – Composition/Information on Ingredients:**

Product Description/Components: Exfoliated vermiculite powder or granules,  
CAS# 1318-00-9

Hazardous ACGIH

Ingredients CAS# % TLV, mg/cu.m. NIOSH, mg/cu.m OSHA PEL, mg/cu.m

Quartz 14808-60-7 <0.1 0.025 (Respirable) 0.05 (Respirable) 0.1 (Respirable)

LD<sub>50</sub>: Not Available LC<sub>50</sub>: Not Available

Product is tan flakes, granules or powder with no odor. Dusts may cause irritation of eyes, skin, mucous membranes and respiratory tract. Wear appropriate personal protective equipment. Keep individuals not involved in the cleanup out of the area. Pick up released product with appropriate implements and return to original container if reusable. If not reusable, place in appropriate containers for disposal. Although the product itself is non-hazardous, material collected during clean up operations may be contaminated and should be treated as hazardous unless specific testing, including TCLP, shows the collected material to be non-hazardous. Product is quite inert and is not expected to present an environmental hazard.

### **SECTION 4 – First Aid Measures:**

Skin Contact: Wash off with soap and water

Eye Contact: Flush eyes with generous amounts of water for at least 5 minutes.

Inhalation:

Remove to fresh air. Seek medical attention if victim is not breathing or uncomfortable.

Ingestion: Do not induce vomiting. Seek medical attention if victim is not breathing or uncomfortable.

### **SECTION 5 - Fire Fighting Measures:**

Flammable: Non Flammable

Means of Extinction: Use extinguishing media appropriate for surrounding material.

Flashpoint (°C) and Method (oc or cc): N/A

Upper Flammable Limit (% by volume): N/A

Lower Flammable Limit (% by volume): N/A

Autoignition Temperature (°C): N/A

Explosion Data - Sensitivity to Impact: N/A

Explosion Data - Sensitivity to Static Discharge: High airborne concentrations of dusts are susceptible to explosions.

Hazardous Combustion Products: N/A

NFPA: Health: \*(Refer to MSDS), Flammability: 0, Reactivity: 0, Other: None

HMIS Ratings: Health: \*(See MSDS), Flammability: 0, Reactivity: 0, Personal Protection: E

### **SECTION 6 - Accidental Release Measures:**

Leak and Spill Procedures: Normal clean-up procedures. Care should be taken to avoid causing dust to become airborne. Vacuum cleaning systems are recommended. Wetting spilled material with water may control dust and make clean up easier.

### **SECTION 7 - Handling and Storage:**

Handling Procedures and Equipment: Avoid creating unnecessary dust  
Storage Requirements: Store with other dusty materials, away from products that could be affected by dust.

### **SECTION 8 - Exposure Control/Personal Protection COMMENTS:**

Exposure Limits

ACGIH TLV: 10 mg/m<sup>3</sup> total dust

3 mg/m<sup>3</sup> respirable dust

OSHA PEL: 15 mg/m<sup>3</sup> total dust

5 mg/m<sup>3</sup> respirable dust

Engineering Controls

General: Good housekeeping rules apply

Local Exhaust from work stations using this material

Recommended Personal Protective Equipment:

- Plastic or Rubber Gloves if skin irritation occurs
- Respirator – NIOSH/OSHA approved dust respirator adequate for contaminant concentrations encountered.
- Eye protection recommended
- Disposable footwear for frequent handling of this material
- Coveralls for frequent handling of this material

### **SECTION 9 – Physical and Chemical Properties:**

Physical State: Solid Powder or granules

Odor and Appearance: Tan powder or granules with no odor

Odor Threshold (ppm): N/A

Specific Gravity: 2.5 to 2.7

Vapor Density (air=1): N/A

Vapor Pressure (mmHg): N/A

Evaporation Rate: N/A

Boiling Point (°C): N/A

Freezing Point (°C): N/A  
pH: 6.5 – 7.5, as 10% slurry in distilled water  
Coefficient of Water/Oil Distribution: N/A  
Solubility in Water: Negligible  
Visual Identification Recommended

### **SECTION 10 - Stability and Reactivity:**

Chemically Stable?: Yes  
Incompatibility with other substances  
Yes: Hydrofluoric acid (HF)  
Reactivity, and under what conditions?: Toxic silicon tetrafluoride gas will result with contact with hydrofluoric acid.  
Hazardous Decomposition Products: See above

### **SECTION 11 - Toxicological Information:**

Effects of Acute Exposure: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), or in case of inhalation (irritant).  
Effects of Chronic Exposure:  
Irritancy of Product: Potential IRRITANT for Skin Sensitization,  
Respiratory Sensitization: Upper Respiratory Irritant: May aggravate pre-existing respiratory conditions. Long-term inhalation of respirable crystalline silica can cause disabling lung disease (silicosis).  
Carcinogenicity: These products contain less than 0.1% crystalline silica, and few particles of respirable size, hence present very low risk.  
IARC: Not reviewed  
ACGIH: PNOS (Particulates Not Otherwise Specified), Not carcinogenic  
Reproductive Toxicity: Not available  
Teratogenicity: Not established  
Embryotoxicity: Not available  
Mutagenicity: Ames: Negative results reported (Salmonella typhimurium, Metabolic Activation: with/without).

### **SECTION 12 – Ecological Information:**

Aquatic Toxicity: Low hazard for usual industrial or commercial handling. Approved for use in soils.

### **SECTION 13 – Disposal Considerations:**

Waste Disposal: Dispose of this product in accordance with all applicable local, state and Federal regulations.

**SECTION 14 – Transport Information:**

Special Shipping Information

DOT: No special requirements

IMO: Non-hazardous ICAO: Non-hazardous

**SECTION 15 – Regulatory Information:**

WHMIS CLASSIFICATION: D2B (Toxic)

OSHA: Label as required by Hazard Communication Standard 29 CFR 1910.1200 (f)  
and

applicable state and local laws and regulations

TSCA: Included as a naturally occurring material.

**SECTION 16 – Other Information:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Information provided in this document is believed to be accurate as of December 31, 2015 and may be subject to change without notice. The information is provided in good faith to comply with applicable federal and state laws. However, no warranty or representation with respect to such information is intended or given. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.