



## Safety Data Sheet Environmental Sweeping Compound

**Product Name:** Enviro - Sweep  
**MSDS Date:** Update 4/22/2015, revised 7/31/15  
**Mfg.:** Frantz Company, Inc.  
12314 W. Silver Spring Dr.  
Milwaukee, WI 53225

**Product Info/Emergency Telephone:** 414-462-8700

**Product Identification:**

**Chemical Name:** N/A

**Formulation Components:**

- 1) Water
- 2) Wood Dust
- 3) Silica Sand

Sweeping compound is used in cleaning floors. It is spread on floors then swept up. Environmental sweeping compound is used on unfinished concrete and wood floors.

**Health Hazard Data:**

None



Skin irritation can be avoided by wearing gloves when using sweeping compound. If contacted with skin wash thoroughly with soap and water.

**Chemical Name:** N/A

**Formulation Components:**

- 1) Water
- 2) Wood Dust
- 3) Silica Sand

The percentage of composition of these components is a trade secret.

**Routes of Exposure and Signs and Symptoms of Exposure:**

**Eye Contact:** Swelling, discomfort associated with foreign substance in eye

**Ingestion:** Mild discomfort, vomiting

**Emergency and First Aid Procedures:**

**Inhalation:** If inhalation occurs, remove personnel from contaminated area to fresh air

**Eye Contact:** Flush with water, refer to physician

**Skin Contact:** Wash thoroughly with soap and water

**Ingestion:** Induce vomiting and consult physician immediately

**Fire and Explosion Data:**

**Flash Point and Method:** 345° F COC Autoignition T

**Flammable Limits:** Upper-N/A, Lower-N/A

**Extinguishing Media:** Water, Foam, CO<sub>2</sub>

**Special Fire Fighting Procedures:** NIOSH/MSHA self-contained breathing apparatus should be provided for confined areas. Do not enter any enclosed or confined fire space without proper protective equipment.

**Spill/Leak Procedures:**

Sweep into proper receptacle

Avoid airborne dust

Wear personal protective equipment

Dispose in accordance with local, state, and federal regulations

**Handling and Storage:**

Store material in a dry area with containers tightly closed

Avoid physical damage to containers and avoid creating airborne dust

**Protective Equipment:**

NIOSH approved dust respirator

Chemically resistant gloves are suggested for handling of material

Safety glasses are required and a protective coverall is optional

**Occupational Exposure Limits:**

Sawdust – OSHA recommends standard maximum permissible concentration 5.0 mg/M<sup>3</sup> at an 8-hour time weighted shift

Oil – OSHA recommends standard maximum permissible concentration 5.0 mg/M<sup>3</sup> as determined by a full-shift sample up to an 8-hour working day

Sand – NIOSH recommends standard maximum permissible concentration of 0.05 mg/M<sup>3</sup> as determined by a full shift sample up to 10 hour working day, 40-hour work week

**Physical Data:**

**Boiling Point:** N/A

**Freezing Point:** N/A

**Specific Gravity:** 1.5

**Melting Point:** 844° C

**Solubility in Water:** N/A

**Reactivity in Water:** N/A

**Appearance and Odor:** Sawdust-Water;

**Reactivity Data:**

**Incompatibilities:** Strong acids, Alkalies, and Oxidizers

**Additional Information:**

Always change clothes and wash hands and face after handling this material

Avoid creating airborne dust

Do not store product with food and/or tobacco products

**Ecological Information:** No data is available.

**Waste Disposal Method:** Product and Packaging waste do not dump in sewers or into any body of water. Please follow all local regulations regarding disposal.

**Transport Information:** Not classified as hazardous for transportation.

**Regulatory Information:** Not classified as hazardous material

**Other Information:**

**Disclaimer:** This information is based on the data presently available and to the best of our knowledge is accurate. But, Frantz Company, Inc. make no warranty, expressed or implied, regarding the accuracy of this data or the results obtained from its use; and, any use of the material itself or in combination with any other material or any process is the sole responsibility of the user.

**Frantz Company Inc.**  
PO Box 344  
Butler, WI 53007  
(414) 462-8700  
FAX: (414) 462-6655